800828

ENVIRONMENTAL LEVELS OF RADIOACTIVITY FOR THE OAK RIDGE AREA

(Report for Period, January - June, 1965)

Compiled by the

Applied Health Physics Section
Health Physics Division

OAK RIDGE NATIONAL LABORATORY

APPROVAL FOR RELEASE

Document: # Unnumbered (18 pages); Date ND;
Title/Subject ENVIRONMENTAL LEVELS OF RADIOACTIVITY
FOR THE OAK RIDGE AREA (Report for Period,
June, 1965)
Approval for unrestricted release of this document is authorized by the Oak
Ridge K-25 Site Classification and Information Control Office, Martin
Marietta Energy Systems Inc., PO Box 2003, Oak Ridge, TN 37831-7307.

Date

K-25 Classification & Information Control Officer

#500

Introduction

Radioactive waste materials arising from the operation of atomic energy installations at Oak Ridge are collected, treated, and disposed of according to their physical states.

Solid wastes are buried in a Conasauga shale formation. This shale has a marked ability to fix radioactive materials by an ion exchange mechanism.

Liquid wastes which contain long-lived fission products are confined in storage tanks or are released to trenches located in the Conasauga shale formation. Low level liquid wastes are discharged, after preliminary treatment, to the surface streams.

Air that may become contaminated by radioactive materials is exhausted to the atmosphere from several tall stacks after treatment by means of filters, scrubbers, and/or precipitators.

This report presents data on the environmental levels of radioactivity for the Oak Ridge Area and compares the data with established maximum permissible concentrations.

Air Monitoring


Atmospheric contamination by long-lived fission products and by fall-out occurring in the general environment of East Tennessee is monitored by two systems of monitoring stations. One system comsists of eight stations which encircle the plant area (Fig. 1) and provide data for evaluating the impact of all Oak Ridge Operations on the immediate environment. A second system consists of seven stations encircling the Oak Ridge Area at distances of from 12 to 75 miles (Fig. 2). This system provides data to aid in evaluating local conditions and to assist im determining the spread or dispersal of contamination should a major incident occur. Sampling for radioactive particulates is carried out by passing air continuously through a filter paper. Airborne radioactive finding is monitored in the immediate environment of the plant areas by passing air through a cartridge containing activated charcoal. Data collected are accumulated and tabulated in average $\mu c/cc$ of air sampled.

Atmospheric contamination by alpha-emitting materials, interpreted as uranium, is determined by taking continuous air samples at three locations on a five-mile radius from the Oak Ridge Gaseous Diffusion Plant (Fig. 3).

Milk Monitoring


Raw milk is monitored for ¹³¹I and ⁹⁰Sr by the collection and analysis of samples from twelve sampling stations located within a radius of 50 miles of ORNL. Samples are collected weekly at each of eight stations

STATION SITES FOR PERIMETER AIR MONITORING SYSTEM



STATION SITES FOR REMOTE AIR MONITORING SYSTEM

Figure 2



SAMPLING POINTS OF OUTSIDE ENVIRONS -- ORGEP AIR

Sampling Location - Five Miles from Planz

Figure 3

located on the fringe of the Oak Ridge Area. Four stations, located more remotely with respect to Oak Ridge Operations, are sampled at a rate of one station each week. The purpose of the milk sampling program is two-fold: first, samples collected in the immediate vicinity of the Oak Ridge Area provide data by which one may evaluate possible exposure to the neighboring population resulting from waste releases from Oak Ridge Operations; second, samples collected at the more remote stations provide background data which are essential in establishing the proper index for the evaluation of data obtained from local samples.

Water Monitoring

Large volume, low level liquid wastes originating at Oak Ridge National Laboratory are discharged, after some preliminary treatment, into the Tennessee River system by way of White Oak Creek and the Clinch River. Liquid wastes originating at the Oak Ridge Gaseous Diffusion Plant and the Y-12 Plant are discharged to Poplar Creek and thence to the Clinch River. Releases are controlled so that resulting average concentrations in the Clinch River comply with the maximum permissible levels for populations in the neighborhood of a controlled area as specified by AEC Manual, Chapter 0524. The concentration of radioactivity leaving White Oak Creek is measured and concentration values for the Clinch River are calculated on the basis of the dilution provided by the river.

Radioactive liquid wastes are sampled at a number of locations as shown in Figs. 4 and 5. Samples are taken at a number of locations in the Clinch River, beginning at a point above the entry of wastes into the river and ending at Center's Ferry near Kingston, Temmessee. Stream gauging operations are carried on continuously to obtain dilution factors for calculating the probable concentrations of wastes in the river.

Samples are analyzed for the long-lived beta emitters, for uranium, and for the transuranic alpha emitters.

Analyses are made of the effluent for the long-lived radionuclides only, since cooling time and hold-up time in the waste effluent system is such that short-lived radionuclides are normally not present. The concentrations of those isotopes present in significant amounts are determined by analysis. A weighted average maximum permissible concentration for water, $(MPC)_w$, for the mixture of radionuclides is calculated on the basis of the isotopic distribution using the MPC values of each isotope as specified by AEC Manual, Chapter $0524.^1$ The average concentrations of gross beta activity in the Clinch River are compared to the calculated $(MPC)_w$ values.

¹ AEC Manual, Chapter 0524, Appendix, Annex 1, Table II.

WATER SAMPLING LOCATIONS




Figure 4

UNCLASSIFIED ORNL-LR-DWG. 49222R2




Figure 5

The concentration of uranium is compared with the specific $(MPC)_w$ value for uranium.

Gamma Measurements

External gamma radiation levels are measured monthly at a number of locations in the Oak Ridge Area. Measurements are taken with a Geiger-Müller tube at a distance of three feet above the ground, and the results are tabulated in terms of mR/hr.

Discussion of Data

Data on the environmental levels of radioactivity for the first half of 1965 in the Oak Ridge and surrounding areas are presented in Table I through Table IX.

The average air contamination level for gross beta activity, as shown by the continuous air monitoring filter data, for both the immediate and remote environs of the plants was 0.28% of the maximum permissible concentration for populations in the neighborhood of a controlled area. This value is approximately 30% lower than those for the last half of 1964 and is no higher than the average of those measured in other areas of the United States and reported by the U.S. Public Health Servic Radiation Surveillance Network for the period January through April, 1965.

The average concentration of ¹³¹I in air in the immediate environs of the plants was 0.022 x 10^{-12} µc/cc (Table II). This is approximately 0.022% of the maximum permissible concentration for populations in the neighborhood of a controlled area.

The average airborne alpha activity in the environs of the ORGDP, five miles from ORGDP, was 4.0% of the maximum permissible concentration for populations in the neighborhood of a controlled area.

The average concentrations of ¹³¹I in raw milk in the immediate and remote environs of the Oak Ridge Area were 8.7 pc/l and 5.4 pc/l, respectively. These values fall within the limits of FRC Range I if one assumes the average intake per individual to be l liter of milk per day. The maximum concentration observed in any one milk sample was 75 pc/l. This value was measured in a sample collected the week of May 30 through June 5, 1965. During this time the East Tennessee Area was experiencing an increase in fallout from weapons testing. Laboratory analyses of samples of fallout confirmed the presence of fresh fission products consistent with the timing of the announced nuclear detonation on the Chinese mainland, May 14, 1965.²

Radiological Health Data, Vol. 6, No. 6, p. 332 (June 1965).

The average concentration of ⁹⁰Sr in raw milk for both the immediate and remote environs of the controlled area was 17 pc/1. This level falls within FRC Range I for transient rates of daily intake of ⁹⁰Sr for application to the average of suitable samples of an exposed population.

The calculated average concentration of radioactivity in the Clinch River at Mile 20.8, the point of entry of most of the wastes, and the measured average concentration at Mile 4.5, near Kingston, Tennessee, were 4.4 x 10^{-8} µc/ml and 2.8 x 10^{-8} µc/ml, respectively. These values are 0.86% and 0.73% of the weighted average maximum permissible concentrations (MPC)_w. The average concentration of transuranic alpha emitters in the Clinch River at Mile 20.8 was 1.0 x 10^{-10} µc/ml which is approximately 0.002% of the weighted average (MPC)_w value.

The average activity of natural uranium materials in the Clinch River, reflecting the effects of all Oak Ridge plants, was < 0.01% of the (MPC)_w for uranium.

The average external gamma radiation measured in the town of Oak Ridge and at the perimeter of the Oak Ridge Area was O.Ol2 mR/hr, which is the same as that level measured in the early period prior to Oak Ridge operations.

Conclusion

Surveillance of the radioactivity in the Oak Ridge environs indicated that the major part of the radioactivity detected continues to be the result of fallout from weapons testing. While some low level radioactivity is being released to the environment from plant operations, the resulting concentrations in both the atmosphere and surface streams of the Oak Ridge environment are well below established maximum permissible concentrations and intake guides for the neighboring population.

TABLE I
CONTINUOUS AIR MONITORING DATA

Long-Lived Gross Beta Activity of Particulates in Air

Station Number	Location	Number of Samples Taken		of 10-13 ; Minimum b		(MPC) _a c
HP-31 HP-32 HP-33 HP-34 HP-35 HP-36 HP-37 HP-38 Average	Kerr Hollow Gate Midway Gate Gallaher Gate White Oak Dam Blair Gate Turnpike Gate Hickory Creek Bend East of EGCR	Perimeter Stat 26 26 26 26 26 26 26 26 26 26 26	10ns 4.9 5.4 5.8 5.8 5.0 6.1 5.5	0.70 0.98 0.47 0.96 0.82 1.1 0.77 0.90 0.84	2.6 2.9 2.6 2.9 3.1 2.5 3.3 2.8	0.26 0.29 0.23 0.26 0.29 0.31 0.25 0.33
HP-51 HP-52 HP-53 HP-55 HP-56 HP-57 Average	Norris Dam Loudoun Dam Douglas Dam Cherokee Dam Watts Bar Dam Great Falls Dam Dale Hollow Dam	Remote Static 26 26 26 26 25 25 25 26		0.91 0.08 0.47 0.51 0.61 0.77 0.78	3.4 2.9 2.9 2.7 2.8 2.8	0.33 0.24 0.29 0.29 0.29 0.27 0.28

^aMaximum weekly average concentration.

Minimum weekly average concentration.

 $^{^{\}rm C}({\rm MPC})_{\rm a}$ is taken to be 10⁻¹⁰ ${\rm \mu c/cc}$ as specified in AEC Manual, Chapter 052⁴, Appendix, Annex 1, Table II.

^dSamples collected on daily schedule beginning 5/7/62. Maximum and minimum daily average concentrations were 11 x 10^{-13} $\mu c/cc$ and < 0.2 x 10^{-13} $\mu c/cc$, respectively.

TABLE II

CONCENTRATION OF 131 I IN AIR AS MEASURED BY THE PERIMETER AIR MONITORING STATIONS

	Unit	s of 10 ⁻¹²	μc/cc	%
Number of Samples	Maximum	Minimuma	Average	(MPC) _a b
208	0•24	< 0.010	0.022	0.022

Minimum detectable amount of ^{131}I is 20 d/m. At the average sampling rate used, this corresponds to approximately 0.010 x 10^{-12} $\mu\text{c/cc}$. In averaging, one-half of this value, 10 d/m, is used for all samples showing a total amount of ^{131}I less than 20 d/m.

 $^{^{\}rm b}({\rm MPC})_{\rm a}$ is taken to be 1 x 10 $^{-10}$ $\mu c/cc$ as specified in AEC Manual, Chapter 0524, Appendix, Annex 1, Table II.

TABLE III

OAK RIDGE GASEOUS DIFFUSION PLANT AIR MONITORING DATA

January - June, 1965

	Avg.	% (MPC) _a **			4.0
		(MPC)a			20.0
					0 . 8
Units of 10 ⁻¹³ µc/cc	Plant	North North East South West Avg.	8	< 1	6.0
Units o	Direction from Plant	North East	5	 	0.8
	Ω	North	77	< 1	9.0
			Max.	Min. < 1	Avg.
		*			
	No. of	Samples*	1/01/1		
		Analyses Sample	Gross Alpha 1404		

* Normal Sampling Frequency: Continuous, averaged over 8 hours.

^{**} Maximum permissible concentration for continuous exposure of the general public.

TABLE IV

CONCENTRATION OF 131 IN RAW MILK

Location		pe/1	
	Maximum	Minimum*	Average
Immediate Environs	75	< 10	8.7
Remote Environs	12	< 10	5-4

^{*}Minimum detectable concentration of 131 I is 10 pc/l. In averaging, one-half of this value, 5 pc/l, was used for all samples showing a concentration less than 10 pc/l.

TABLE V

CONCENTRATION OF ⁹⁰SR IN RAW-MILK

January - June, 1965

Togetien		pc/l	
Location	Maximum	Minimum*	Average
Immediate Environs	55	< 2.0	-
Remote Environs	32	< 2.0	

*Minimum detectable concentration of *OSr in milk: 2 pc/l. In averaging, one-half of this value, I p./l, was used for all samples showing a concentration less than 2 pc/l.

TABLE VI

CALCULATED AVERAGE CONCENTRATION OF RADIOACTIVITY
IN THE CLINCH RIVER AT MILE 20.8

Number of	Uni	ts of 10 ⁻⁷ μc/	ml	% of (MPC)w
Samples Taken	Maximum ^a	Minimum ^b .	Average	p or (rec)
182	1.7	0.11	⊖. 4+4;	0.86

a Maximum weekly average.

b Minimum weekly average.

TABLE VII

AVERAGE CONCENTRATION OF MAJOR RADIOACTIVE CONSTITUENTS IN THE CLINCH RIVER

January - June, 1965

				Unit	Units of 10 ⁻⁸ µc/ml	uc/ml) to
Location	90Sr		¹⁴⁴ Ce ¹³⁷ Cs	106Ru	ဝ၁ _{ဝ 9}	qN _{g6} - 17 ₉₆	Average Beta Activity	(MPC) _w	(MPC) _W
Mi. 41.5 ^b	0.08	0.08 0.03 < 0.01	< 0.01	0.16	*	*	0.27	100	0.27
Mi. 20.8^{c}	0.13	0.13 < 0.01	0.04	1.5	0.25	< 0.01	†* †	510	0.86
Mi. 4.5	0.16	0.16 0.04	0.25	1.7	0.27	0.02	2.4	330	0.73

^aWeighted average $(MPC)_{w}$ calculated for the mixture using $(MPC)_{w}$ values for specific radionuclides specified by AEC Manual, Chapter 052^{4} , Appendix, Annex 1, Table II.

Bampling station moved from Clinch River Mile 33.2 to Mile 41.5 about January 1, 1962.

CValues given for this location are calculated values based on levels of waste released and the dilution afforded by the river; they do not include amounts of radioactive material (e.g., fallout) that may enter the river upstream from CRM 20.8.

*None detected.

TABLE VIII

URANIUM CONCENTRATION IN THE CLINCH RIVER

Sampling Point	Type of	No. of		Units of	Units of 10°8 µc/ml		
	Analyses Made	Samples*	Samples*. Maximum** Minimum** Average**	Minimum**	Average**	(MPC) _W	% (MPC) _w
Upstream from ORGDP	Uranium Concentration	2	< 0.1	< 0.1	< 0.1	2000	< 0.01
Downstream from ORGDP	Uranium Concentration	CV.	< 0.1	< 0.1	< 0.1	. 5000	< 0.01

^{*}Normal Sampling Frequency: Continuous, composited over one quarter.

^{**}No uranium was detected in Clinch River water samples during this period. Minimum detectable concentration of uranium in river water is 0.1 x 10-8 $\mu c/ml$.

TABLE IX

EXTERNAL GAMMA RADIATION LEVELS

mR/hr

January - June, 1965

Station Number	Location	Jan.	Feb.	March Apr.		May	June	Average
1	Solway Gate	0.013	0.011	0.028	}	0.010 0.009	*	0.014
a	Y-12 East Portal	0.011	0.011	0.011	0.009	0.009 0.011	*	0.011
8	Newcomb Road, Oak Ridge	0.012	0.011	0.012	0.010	0.010 0.011	*	0.011
#	Gallaher Gate	0.014	0.012	0.012	0.013	0.013 0.010	*	0.012
5	White Wing Gate	0.011	0.011	0.012	0.010	0.010 0.012	*	0.011
Average		0.012	0.012 0.011	0.015	0.015 0.010 0.011	0.011	*	0.012

These readings were taken with a calibrated Geiger-Müller tube at a distance of three feet above the ground. Note:

The background in the Oak Ridge area in 1943 was determined to be approximately 0.012 mR/hr.

*No background readings taken this month.

ChemRisk Document Request Transmittal Form (This section to be completed by ChemRisk)

S. Sandberg	, ISD	
Name	Division	is requested to provide the following document
Address		
Date of Request 12/10	Expected rece	ipt of document 12/21
Title of requested document_	Env. Levels	of Radioaclivily
Document Number 800	25 8 84 - 80083)	800828
Access Number of Documen	t	Date of Document 1962-1965
(This section to be complete	ed by Derivative Class	ifier)
Derivative Classifier 7.	G. Jordan	Phone 4 1645
Date document transmitted to	Dr. Quist 1/15/9	3 1/29 (93
Date release received from I	Dr. Quist OK 0-8	2 1/22/83
PUBLIC RELEASE STAME	attached to each copy	of document (YES NO)
Date document sent to repro	duction	Expected Return_
Delivered to DRC by		Date
(This section to be complete	ed by DRC)	
Received by DRC	Date	
Processed		
Mailed		

OAK RIDGE K-25 SITE DOCUMENT

1 K-25CO: PC(4710) FORM

JLamb K25CO-RC(4710) FORM

JLamb K25CO-RC(4710) FORM Person requesting release JENNIFER LAMB (CHEMRISK 4-0745 Mailing Address K-1200 MS-7262 or Organization Date by which release is required (Standard processing time is 5 working days. Some documents require special review and __a processing time will be longer). Note: Two copies of the document must generally be provided to the Classification and Information Control Office with this request, Only one copy of photos and videotapes is required. Documents that include photos must be accompanied by "originals" of the photos. Approval of request for Classification and Information Control Office to release document (department head or higher): Signature: Date DOCUMENT DESCRIPTION (to be completed by requester) UNNUMBERED/800828 20 Pages Document number Document title ENVIRONMENTAL LEVELS OF RADIOACTIVITY FOR THE OAK RIDGE AREA (REPORT FOR PERIOD JANUARY - JUNE, 1965) Author(s) (indicate other divisions or organizations, if applicable) APPLIED HEALTH PHYSICS SECTION (ORNL) Document type (See Doc. Prep. Guide, Chs. 1 and 2, for definitions of document types): Formal Report Progress Report ☐ Informal R&D Report ☐ Abstract Drawing Administrative Internal Technical Data ☐ Correspondence ☐ Photo Other Visuals Journal Article (identify journal): Oral Presentation (identify meeting, sponsor, location, date): Will oral presentation be published in program, booklet, brochure, etc.? ☐ Yes □ No ☐ Not Known Will copies of the oral presentation be distributed \square before, \square after, \square during the meeting? \square No distribution will be made. Other (specify): Purpose of release HEALTH STUDY FEASIBILITY PROJECT Previously cleared documents containing similar information FT No is copyrighted material contained in this document? (If present, attach release.) Remarks CLASSIFICATION INFORMATION (to be obtained by requester) Was the work reported in this document funded, in whole or in part, by a classified program at Martin Marietta Energy Systems, Inc.? ☐ No ☐ Yes (Name of program: Is the subject area of this document closely related to a prior or current classified program at Martin Marietta Energy Systems, inc.? ☐ No ☐ Yes Within the Department of Energy?

No
Yes Name or Description of applicable program(s) Additional remarks This document contains no classified information.

Derivative Classifier signature

DISTRIBUTION LIMITATIONS (I	fany) (completed by requester)
Unrestricted, unlimited	
Distribution may be limited because this document contains informati	on that is:
☐ Unclassified Controlled Nuclear Information * ☐ Applied	Technology * Export Controlled *
☐ Naval Nuclear Propulsion Information * ☐ Gov't Co	nfidential Commercial Information * Proprietary
☐ Sensitive Nuclear Technology * ☐ Small Bu	siness Innovation Research *
☐ Safeguards Information * ☐ Coopera	tive R&D Agreement *
* Ge	enerally identified by sponsor
	•
Remarks:	
nomeans.	
DATENT INFORMATION (
PATENT INFORMATION (completed by requester)
Does this document disclose any new equipment, process, or materi	ai? 🔲 Yes 🔲 No
If yes, list the patent significance and identify page number(s) and lin	e number(s) in the space immediately following
(or attach separate pages).	o nonector in the space warroundery to nowing
PATENT SECTION ACTION (completed by Patent Section upo	n request by the Classification and Information Control Office)
☐ Document may be released for publication ☐	Document must be reviewed by DOE Patent Group before release
Document contains patentable information	tion and may not be released at this time
Remarks	
Patent Section Representative	Date
CLASSIFICATION AND INFORMATION CONTROL OFFICE ACT	ON (completed by Classification and information Control Office)
Classification Office	Annual formula and the bound for the bound f
Action Taken:	☐ Approved for release with changes (see below)
☐ Approved for release without change	
Classification Officer signature	Date
Technical Information Office Action Taken: Not approved for release (see below)	Approved for release with changes (see below)
Approved for release without change	
to Chemilist.	
The American	
Technical Information Officer Signature (Aurin)	(b) Date 1/24/43
Send to OSTI? Yes No	
Deline IO COTHE THES THE	Category Distribution: